

kagoshima kokutai



					Annu Fause Annu Suppling
Oil Pattern Distance	38	Reverse Brush Drop	38	Oil Per Board	50 ul
Forward Oil Total	25.35 mL	Reverse Oil Total	11.1 mL	Volume Oil Total	36.45 mL
Tank Configuration	Only A	Tank A Conditioner	PRODGY	Tank B Conditioner	PRODGY

	START	STOP	LOAD5	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	6	10	222	0.0	7.0	7.0	11100
2	4L	4R	4	14	132	7.0	14.9	7.9	6600
3	5L	5R	4	14	124	14.9	22.8	7.9	6200
4	6L	6R	1	14	29	22.8	24.7	1.9	1450
5	2L	2R	0	18	0	24.7	38.0	13.3	0

	START	STOP	LOADS	SPEED	CROSSED	START	END	FEET	T.OIL
1	2L	2R	0	26	0	38.0	23.0	-15.0	0
2	9L	8R	2	18	48	23.0	17.9	-5.1	2400
3	8L	7R	3	18	78	17.9	10.3	-7.6	3900
4	5L	4R	3	10	96	10.3	6.1	-4.2	4800
5	2L	2R	0	10	0	6.1	0.0	-6.1	0

Cleaner Ratio Main Mix

Cleaner Ratio Back End Mix

NA

Cleaner Ratio Back End Distance

NA

Buffer RPM: 4 = 720 | 3 = 500 | 2 = 200 | 1 = 50

WINDING ROAD - 2839

This oil pattern uses a distance of 39 feet with very little downlane help to guide the ball into the pocket. Because of the lower ratios towards the end of pattern, the greatest factor on how the WINDING ROAD will play is the

		J		:	ş	2		,	-			=	3		;	_		**	=			_	_				
\prod																											
\parallel	t	ŀ			l		ŀ			\mid					ŀ			I			1		+	1	t	t	ť
Щ	l	L																									S
																		I									_
	Ī																								1		4
$\dagger \dagger$	t																								†	t	Y
Ш	l	L																									×
																								I			2
	Ī																							I	Ī		K
	Ī	Ī																						I	I		00
																											¥
																											ç
	1																			1	1			1	I	1	

Item	3L-7L:18L-18R	8L-12L:18L-18R	13L-17L:18L-18R	18L-18R:17R-13R	18L-18R:12R-8R	18L-18R:7R-3R
Description	Outside Track:Middle	Middle Track:Middle	Inside Track:Middle	Mlddle: Inside Track	Middle:Middle Track	Middle:Outside Track
Track Zone Ratio	1.67	1.02	1	1	1	1.53

